

# STEAM SYSTEMS

Critical Components of Detailed Design Drawings



RMF Engineering  
Reliability. Efficiency. Integrity.


# Steam System Designs

- Communicate Design Concepts
  - Expansion: Anchoring and Movement
  - Flow: Draining and Trapping
  - Access: Maintenance, Egress, and Water!
- What you should expect
- Discussion

# System Schematics

- Expansion Concepts
  - Anchors
  - Joints
  - Loops
- Flow of Systems
  - Traps, Valves, Service Points
- Problems?

# Campus Steam Schematic



# Piping Expansion Compensation




**Horizontal Loops**



**Vertical Loops**



**Externally Pressurized  
Bellows Joint**



**Slip Pack Joint**



**Ball Joint**



**Bellows Joint**



# Expansion – Anchoring and Movement

- Tunnel Systems
  - Typically Anchors, Guides, Slides and Joints
- Direct Buried Systems
  - Typically Anchors and Loops
  - Sometimes Joints
- Mixed Systems
- Critical to understand Design



# Expansion – Anchor Forces

200 LF 6" SCH STD A106 Carbon Steel  
125 PSIG Sat Steam (353°F, 50°F ambient)

Guided Loop

559 LBF  
(Thermal)

Externally Pressurized Bellows


9,435 LBF  
(Hydrostatic)

Slip Type Expansion Joint

10,312 LBF  
(Thermal)

# Forces, Stresses, Supports and Deflections


Determine Anchor Locations  
Compliance with ASME B31.1  
Guides and Supports  
Deflection Calculations





# Anchor Design

- Control Movement, transmit forces



## ANCHOR NOTES:

1. REFER TO MECHANICAL DRAWINGS FOR PIPE ANCHOR LOCATIONS. COORDINATE ANCHOR PLATE SIZES WITH PIPE SHOP DRAWINGS.
2. ALL ANCHOR PLATES SHALL BE HOT-DIP GALVANIZED. TOUCH-UP WELDS WITH COLD GALVANIZING PAINT.
3. SUBMIT ANCHOR SHOP DRAWINGS FOR ENGINEER REVIEW.
4. COORDINATE ANCHOR FABRICATION AND INSTALLATION WITH MECHANICAL.

2  
54.04

HPS & PC ANCHOR AT MH-1016 DETAIL  
SCALE: 1 1/2" = 1'-0"

# Supports and Deflections

- Design expected movements of guides and slides




Cold



Hot!

# So far we have...

- ✓ Knowledge of System-
  - ✓ Expansion and Anchoring
  - ✓ Flow
  - ✓ Isolation
- ✓ Detailed Component Design
  - ✓ Anchor Details
  - ✓ Supports, Slides and Guides
  - ✓ Movement of System



EX TUNNEL VAULT I - NEW WORK - 10" HPS ANCHOR

SCALE: 1"=1'-0"



**RMF Engineering**  
Reliability. Efficiency. Integrity.

© 2015 Pearson Education, Inc. or its affiliate(s). All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage or retrieval system, without prior written permission from Pearson Education, Inc. or its affiliate(s).






# System Profile


- Profile design is critical to controlling condensate
- System Schematic – add elevations and traps



# System Profile



# System Profile




# Now we've added...

- ✓ Design and Identify the trapping concepts
- ✓ Detailed Plans
  - ✓ Based on good survey information
- ✓ Detailed Profiles
  - ✓ Get utility crossings identified!


# Vault Details

- Manway Access and Egress
  - Number, Size, Configuration, Covers
- Ladder Position
- Relationship to Service Items
- Mechanical Details
  - Valves, Drip Legs, Traps, Pumps, etc.
- Ventilation
- Waterproofing




# Vault Details

- Valve Position
- Valve Orientation
- Trap Position
  - Removable
  - Expansion
  - Insulation
  - Redundant
  - Testable






# Vault Details



**VALVE VAULT NO. 101**  
SCALE: 3/4"=1'-0"



**SECTION A**  
SCALE: 1/4"=1'-0"

- Supports
- Penetrations
- Auxiliaries




# Ventilation

- Natural Convection
- Forced Ventilation



# Water!

- Waterproofing approach
- Multiple lines of defense
- Backup Plan!





# Waterproofing Systems

- Integrally bonded membrane
- Bentonite / HDPE
- Bituthene Membrane
- Fluid applied system

Grace Below Grade Waterproofing

GRACE

**TREMCO**

**Paraseal**

Grace Below Grade Waterproofing

GRACE

**BITUTHENE<sup>®</sup> SYSTEM 4000**

Self-adhesive HDPE waterproofing membrane with superior tacky compound for use with patented



**RMF Engineering**  
Reliability. Efficiency. Integrity.

# Waterproofing





# Waterproofing – Pipe Penetrations

PROVIDE ASPHALTIC WATERPROOFING  
AROUND INSIDE AND OUT V  
ELASTOMERIC SHEET WATERPROOFING  
REQUIRED OR EXISTING

PACK W/DARK  
NON-FERR  
NON-SHRINK  
6 GAUGE S  
SIZE FOR  
PIPE, AND  
EXTERIOR V

K  
C201




# Waterproofing – Backup Plan

- Steam power
- Electric Pump
- Temporary p



# Waterproofing – Backup Plan

## ■ Gravity Drain



<b>SMITH* JAY B. SMITH MFG. CO.*</b> DIVISION OF SMITH INDUSTRIES, INC. PORT OFFICE BOX 1037 NORTH CANTON, MA 01861 TEL: 508/271-1410 FAX: 508/271-7591 www.jayb.com		LOCATION																																				
<h2>BACKWATER VALVE</h2> <h3>PIT STYLE BACKWATER VALVE</h3>																																						
<p><b>FUNCTION:</b> Used at the base of side walls in pits, where low elevation requires a vertical inlet grate and side outlet roughing. Backwater valve provides protection against backflow which could damage equipment in pit.</p>																																						
<table border="1"> <thead> <tr> <th>A SIZE</th> <th>B x B</th> <th>C x C</th> <th>D</th> <th>E</th> <th>F</th> <th>Free Area SQ. IN. (SQ. CM)</th> </tr> </thead> <tbody> <tr> <td>*03 (80)</td> <td>6 3/4(170) x 9 1/2(240)</td> <td>10 1/4(260) x 12(305)</td> <td>3 (76)</td> <td>11 1/4 (285)</td> <td>2 3/4 (70)</td> <td>15 (97)</td> </tr> <tr> <td>*04 (100)</td> <td>6 3/4(170) x 9 1/2(240)</td> <td>10 1/4(260) x 12(305)</td> <td>3 (76)</td> <td>11 1/4 (285)</td> <td>2 1/4 (67)</td> <td>15 (97)</td> </tr> <tr> <td>05 (125) &amp; 06 (150)</td> <td>7 3/4(195) x 11(280)</td> <td>9 3/4(250) x 13(330)</td> <td>4 (100)</td> <td>13 1/4 (335)</td> <td>1 1/4 (32)</td> <td>24 1/2 (158)</td> </tr> <tr> <td>08 (200)</td> <td>11 1/2(290) x 14 1/2(370)</td> <td>17 1/4(440) x 19(485)</td> <td>4 (100)</td> <td>22 (560)</td> <td>4 3/4 (120)</td> <td>56 (361)</td> </tr> </tbody> </table> <p>*Sized for NO-HUB and/or Service Weight.</p>				A SIZE	B x B	C x C	D	E	F	Free Area SQ. IN. (SQ. CM)	*03 (80)	6 3/4(170) x 9 1/2(240)	10 1/4(260) x 12(305)	3 (76)	11 1/4 (285)	2 3/4 (70)	15 (97)	*04 (100)	6 3/4(170) x 9 1/2(240)	10 1/4(260) x 12(305)	3 (76)	11 1/4 (285)	2 1/4 (67)	15 (97)	05 (125) & 06 (150)	7 3/4(195) x 11(280)	9 3/4(250) x 13(330)	4 (100)	13 1/4 (335)	1 1/4 (32)	24 1/2 (158)	08 (200)	11 1/2(290) x 14 1/2(370)	17 1/4(440) x 19(485)	4 (100)	22 (560)	4 3/4 (120)	56 (361)
A SIZE	B x B	C x C	D	E	F	Free Area SQ. IN. (SQ. CM)																																
*03 (80)	6 3/4(170) x 9 1/2(240)	10 1/4(260) x 12(305)	3 (76)	11 1/4 (285)	2 3/4 (70)	15 (97)																																
*04 (100)	6 3/4(170) x 9 1/2(240)	10 1/4(260) x 12(305)	3 (76)	11 1/4 (285)	2 1/4 (67)	15 (97)																																
05 (125) & 06 (150)	7 3/4(195) x 11(280)	9 3/4(250) x 13(330)	4 (100)	13 1/4 (335)	1 1/4 (32)	24 1/2 (158)																																
08 (200)	11 1/2(290) x 14 1/2(370)	17 1/4(440) x 19(485)	4 (100)	22 (560)	4 3/4 (120)	56 (361)																																
<p><b>NOTE:</b> B.W.V. flapper set at factory to hang in closed position. Pin can be moved to permit flapper to hang open 14" (6) to permit air circulation.</p>																																						
<p><b>REGULARLY FURNISHED:</b>          Duo Cast Iron Body with Backwater Valve and Cast Iron Secured Grate.</p>																																						
<p><b>VARIATIONS:</b></p> <table border="0"> <tr> <td><input type="checkbox"/> Flashing Clamp -C</td> <td><input type="checkbox"/> Less Backwater Valve -LBWV</td> </tr> <tr> <td><input type="checkbox"/> Service Weight Outlet -SW</td> <td></td> </tr> </table>				<input type="checkbox"/> Flashing Clamp -C	<input type="checkbox"/> Less Backwater Valve -LBWV	<input type="checkbox"/> Service Weight Outlet -SW																																
<input type="checkbox"/> Flashing Clamp -C	<input type="checkbox"/> Less Backwater Valve -LBWV																																					
<input type="checkbox"/> Service Weight Outlet -SW																																						
<p><b>OPTIONAL MATERIALS:</b></p> <table border="0"> <tr> <td><input type="checkbox"/> Chrome Plated Face -CP</td> <td><input type="checkbox"/> Galvanized Cast Iron -GI</td> </tr> <tr> <td><input type="checkbox"/> Nickel Bronze Face -NB</td> <td><input type="checkbox"/> Polished Bronze Face -PB</td> </tr> <tr> <td><input type="checkbox"/> Stainless Steel</td> <td></td> </tr> </table> <p>(Specify Fig. 9700)</p>				<input type="checkbox"/> Chrome Plated Face -CP	<input type="checkbox"/> Galvanized Cast Iron -GI	<input type="checkbox"/> Nickel Bronze Face -NB	<input type="checkbox"/> Polished Bronze Face -PB	<input type="checkbox"/> Stainless Steel																														
<input type="checkbox"/> Chrome Plated Face -CP	<input type="checkbox"/> Galvanized Cast Iron -GI																																					
<input type="checkbox"/> Nickel Bronze Face -NB	<input type="checkbox"/> Polished Bronze Face -PB																																					
<input type="checkbox"/> Stainless Steel																																						
<p><b>NOTE:</b> These valves offer protection against backwater surges. Backflow is prevented when valve is not obstructed by debris or sludge. Use for gravity flow only, not for pressurized applications.</p>																																						
DATE 6-29-95 8-17-94 1-18-94 2-10-99	Chg'd Reg Fum, added Metrics Revised Submittal Update Redraw & Chg'd Red Fum	EMB EMB EMB EMB	BS BS BS JCS																																			
WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER <b>7000</b>																																				
REV	DATE	DESCRIPTION	BY																																			



# Design Intent, Details and Schedules

- State Design Intent and Assumptions
- Details, Details, and more Details
- Schedules

EXPANSION JOINT SCHEDULE																			
DESIG.	PIPE SIZE & SERVICE (NPS)	LOCATION	DWG. LOCATION	NORMAL OPERATING CONDITIONS			DESIGN CONDITIONS			HYDRO. TEST PRESSURE (PSIG)	DIST. BETWEEN ANCHORS (FT)	EXPANSION JOINT MOVEMENT				EXPANSION JOINT DESIGN			
				PRES. (PSIG)	HOT TEMP (°F)	COLD TEMP (°F)	PRES. (PSIG)	HOT TEMP (°F)	COLD TEMP (°F)			MAX. OPERATING		RATED		STYLE	DESIGN PRES. THRUST AREA (N²)	DESIGN SEAL FORCE (LBS)	DESIGN BASIS
												EXTENSION (IN.)	COMPRSES. (IN.)	EXTENSION (IN.)	COMPRSES. (IN.)				
EJ-1A	10" 150S	TUNNEL/VH-I	M-201	125	353	70	150	366	70	225	140	0.25	3.4	0.5	4	SLIP-PAKED	90.8	10,000	ATS SLIP-PAKED 10"
EJ-1B	10" 150S	TUNNEL/VH-I	M-201	125	353	70	150	366	70	225	140	0.25	3.4	0.5	4	SLIP-PAKED	90.8	10,000	ATS SLIP-PAKED 10"
EJ-2A	5" 150S	TUNNEL/VH-I	M-201	125	353	70	150	366	70	225	140	0.25	3.1	0.5	4	SLIP-PAKED	24.3	5,000	ATS SLIP-PAKED 5"
EJ-2B	5" 150S	TUNNEL/VH-I	M-201	125	353	70	150	366	70	225	140	0.25	3.1	0.5	4	SLIP-PAKED	24.3	5,000	ATS SLIP-PAKED 5"
EJ-3A	6" PC	TUNNEL/VH-I	M-201	60	180	70	60	180	70	225	140	0.25	1.3	0.5	4	SLIP-PAKED	34.5	6,000	ATS SLIP-PAKED 6"
EJ-3B	6" PC	TUNNEL/VH-I	M-201	60	180	70	60	180	70	225	140	0.25	1.3	0.5	4	SLIP-PAKED	34.5	6,000	ATS SLIP-PAKED 6"

NOTES: 1. INSTALL TEMPERATURE IS CONSIDERED TO BE 70°F.  
2. DO NOT PRESSURIZE JOINTS FOR ANY REASON UNTIL ANCHORS ADJACENT TO JOINT ARE COMPLETE.

PUMP SCHEDULE													
DESIG.	SYSTEM	TYPE	GPM	HEAD PSI	SUCTION X DISCHARGE	MAX. NPSH REQUIRED (FT. WG.)	MOTOR		RPM	% EFFICIENCY	ELECTRICAL (V/PH/42)	BASIS OF DESIGN	REMARKS
							BHP	HP					
CDP-1	CONDENSATE PUMP	END SUCTION	300	85	3" x 2"	14.4	24	30	3560	61	200/3/60	GOULDS 3196 2x3x10	
CDP-2	CONDENSATE PUMP	END SUCTION	300	85	3" x 2"	14.4	24	30	3560	61	200/3/60	GOULDS 3196 2x3x10	

STEAM TRAP SCHEDULE										
DESIG.	SERVICE	TRAP TYPE	TRAP SIZE (IN)	INLET PRES (PSIG)	STEAM TEMPERATURE (°F)		FLOW RATES (LB/HR)		BACKPRESSURE (PSIG)	DESIGN BASIS
					OPERATING	MAXIMUM	OPERATING	MAXIMUM		
STP-1	HPS VAULT 42	INVERTED BUCKET	3/4"	125	353	366	250	450	65	ARMSTRONG 811 SERIES
STP-2	HPS VAULT 42 SUMP PUMP	INVERTED BUCKET	1/2"	125	353	366	50	100	65	ARMSTRONG 811 SERIES
STP-3	HPS VAULT 41	INVERTED BUCKET	3/4"	125	353	366	250	450	65	ARMSTRONG 811 SERIES
STP-4	HPS VAULT 41 SUMP PUMP	INVERTED BUCKET	1/2"	125	353	366	50	100	65	ARMSTRONG 811 SERIES
STP-5	EX HPS VAULT 5	INVERTED BUCKET	3/4"	125	353	366	250	450	65	ARMSTRONG 811 SERIES

# The Checklist

- ✓ System Schematic – Design Intent
- ✓ Expansion Concept – Anchors, Joints, Loops, etc.
- ✓ Draining Concept – Profiles, Traps
- ✓ Flow Concept – Direction, Isolation and Trapping
- ✓ Access, Operability and Maintainability
- ✓ Details Details Details
- ✓ Schedules – Information on Drawings

# Questions?

Thank you!

Vance Nall, PE  
[vance.nall@rmf.com](mailto:vance.nall@rmf.com)



RMF Engineering  
Reliability. Efficiency. Integrity.