

# Auburn University Basketball Arena:

## How Building Data Analytics Achieved Energy and O&M Savings While Improving Comfort and Sustainability

Eric Moore, PE, CEM, Auburn University  
Hadas Webb, CEM, Cimetrics

IDEA 27th Annual Campus Energy Conference  
Atlanta, GA  
February 20, 2014





# Agenda

---

- Auburn University & Cimetrics Collaboration
- Auburn Arena Background
- Case Study Findings:
  - Fan speed control
  - Dehumidification control
  - Damper controls
  - Heat exchanger modification
- Ongoing Commissioning Results
- Questions

# Auburn + Cimetrics Collaboration

---

- University Sustainability Goals
  - American College & University Presidents Climate Commitment (ACUPCC)
  - Carbon neutral by 2050
  - Reduce campus energy intensity 20% by 2020 based on 2006 baseline
- Ongoing commissioning identified **annual** savings
  - Energy: \$444,276
  - CO<sub>2</sub>: 4,560 metric tons
  - Electrical: 2,560 MWh
  - HW: 31,000 kgal
  - CHW: 108,000 kgal
  - Steam: 1,150 mlb
  - Natural gas: 1,257 MCF
- **Cumulative** savings of \$900,000 and 29% reduction in MMBTU/ft<sup>2</sup> between 2008 and 2013



# Auburn Basketball Arena

---

- Built in 2010
- 276,568 ft<sup>2</sup>, \$92.5 million facility
- 9,121 seat main court
- Use: Men's and Women's basketball, Women's gymnastics, music events, camps, commencements
- Additional space: practice courts, locker rooms, weight training, sports medicine, offices, suites & lounges, food prep and service, athletics museum
- Connected to central hot water and chilled water systems

# Issues Identified

---

- Main court AHUs:
  - Supply fan VFDs running at constant speeds
  - Cooling valves 100% open in dehumidification mode
  - Economizer optimization
- Building pressurization
- Domestic hot water heat exchanger configuration
- Chilled water pump differential pressure exceeding setpoint
- AHU operation improvements:
  - Occupancy scheduling
  - Static pressure setpoint reset
  - Damper control
  - Temperature control
- VAV operation improvements

# Arena Data Collection & Reporting


---

- Building automation system (HVAC) data collection, analysis, and reporting by Cimetrics started in Sept. 2011:
  - 2,145 total JCI points polled 24/7/365
  - 15-minute polling frequency
  - 7,798 computed points
  - 200,000+ samples per day
- Equipment monitored and analyzed:
  - 23 air handling units & 19 exhaust fans
  - 5 hot water & chilled water pumps
  - 100 terminal units
  - Multiple system control valves




# Main Court Supply Fan Speed Control

## Original Configuration: 2 fans at 100%




# Main Court Supply Fan Speed Control

## Final Configuration: 4 fans variable speeds






# Main Court Fan Speed Control Results



- 184,500 kWh reduction over 7 month period
- \$9,200 savings over 7 months
- \$15,700 annualized savings
- 72% reduction in electricity consumption

# Main Court Dehumidification Control


## AHU Dehumidification Control - Average Across 4 AHUs






# Main Court Dehumidification Control

## AHU Dehumidification Control and Building Chilled Water



# Main Court AHU Damper Control



## Issues Identified:

- Building Over Pressurization
- Mixed Air Temperature Control
- Economizer Potential
- High CO<sub>2</sub> Levels

## Improvements:


- Building pressure sensors
- Dampers now used to control building pressure, CO<sub>2</sub> levels, and mixed air temperature



# Heat Exchanger Modification

## Issue Identified:

- Instantaneous domestic hot water heaters had three-way valves on primary side.



## Estimated Annual Savings:

- Central Plant - \$10,000

# Energy & Environmental Results

---

- Estimated results based on Cimetrics recommendations and Auburn University implementation
  - Annual savings: \$114,000
  - Annual carbon savings: 1,800 metric-tons CO<sub>2</sub>
- Energy intensity based on actual utility data
  - 2010: 188,476 BTU/ft<sup>2</sup>
  - 2011: 165,950 BTU/ft<sup>2</sup>
  - 2012: 150,447 BTU/ft<sup>2</sup>
  - 2013: 151,290 BTU/ft<sup>2</sup>



# Special thanks to:

---

- Auburn Athletics Department
- Ken Martin – Energy Engineer, Auburn
- Mike Harris – Director of Utilities & Energy, Auburn
- Rick Mitchell – Johnson Controls
- Karim Bibawi – VP of Sales & Marketing, Cimetrics
- Mary Ellen Cantabene – Chief Operating Officer, Cimetrics
- Dean Taylor – Manager of Analytics, Cimetrics



# Questions?

Eric Moore, PE, CEM, Auburn University  
[jem0028@auburn.edu](mailto:jem0028@auburn.edu)

Hadas Webb, CEM, Cimetrics  
[hwebb@cimetrics.com](mailto:hwebb@cimetrics.com)

IDEA 27th Annual Campus Energy Conference  
Atlanta, GA  
February 20, 2014

