

# EVAPCO FOR LIFE



Since 1976  
An Employee-Owned Company  
Commercial HVAC | Industrial Refrigeration  
Power Generation | Industrial Process

FULL SPECTRUM GLOBAL SOLUTIONS



# Important Criteria When Considering Cooling Towers for Your DCP

**Georges Hoeterickx**  
Director Business Development

**Jelle Wagelmans**  
Sales Manager Middle East



# Important Criteria When Considering Cooling Towers For Your DCP


- **Film Fill Types – Materials – Maintenance**
- Cooling Tower Layout
- Thermal Performance Certification (CTI)

# Film Fill types – Materials – Maintenance

- **Types of Fill & Selection Criteria**
- Thermal Performance Ratings
- Material and Mechanical Properties
- Fill Life Time and Maintaining Tower Efficiency

# Fill Selection Criteria


## Splash Type



- The water droplets generated by splashing
- Heat exchange between water droplets surface and air

# Fill Selection Criteria

## Film Type



- Heat exchange between water film surface on PVC sheet and the air


# Fill Film Selection

- Fill is a media to create more **water surface** exposed to the air
- Fill increases the time air-water contact by retarding the progress of water




**Increased heat transfer**


# Fill Selection Criteria



Film Fill



Perforated Sheet



Splash Bars



Splash Grids



Water Quality



# Fill Selection Criteria

The selection of the FILL TYPE depends on the circulating water characteristics:

- Type of water: sea, TSE, potable water
- Type of industry: power, chemical, paper, steel, DCP ...
- Water availability (concentration factor)
- Type of water treatment


# Water Quality

## Fill Fouling Directly Related to Total Suspended Solids (TSS) & Biological Activity

- Origin Suspended Solids in the circulating water:
  - TSS of make up water
  - Dust and airborne particles washed by the cooling tower
  - Dispersants used to control the scaling
- Biological activity controlled with biocides injection

**TSS maximum concentration for each fill is only valid if the Biological activity is controlled !**

# Film Fill Types




**Cross-Flutes**  
**High Efficiency**



FULL SPECTRUM GLOBAL SOLUTIONS




# Cross Corrugated Film Fill Type




- Cross corrugated flutes require (very) good water quality
- Highest specific heat transfer
- Slow water / long air travel → risk for fouling
- Crossed sheet design = high structural rigidity

# Film Fill Types




**Cross-Flutes**  
**High Efficiency**



**Offset-Flutes**  
**Efficient**  
**Low-Fouling**




# Vertically Offset Flute Film Fill Type




- Offset flutes require good water but more forgiving than cross corrugated
- Highly efficient sheet texture and transitions
- Moderately fast water vs. air travel = low fouling risk
- Lower efficiency compensated by low pressure drop


# Film Fill Types



**Cross-Flutes**  
High Efficiency




**Offset-Flutes**  
Efficient  
Low-Fouling



**Vertical-Flutes**  
Anti-Fouling



# Vertical Flute Film Fill Type



- Vertical flutes handle severe water quality well with proper bacterial control
- Efficient sheet texture = very low fouling risk
- Fast water / air travel = very low fouling risk
- Very low pressure drop = better than splash

# Water Quality Comparison

## Biological / Bacteria and Total Suspended Solids

Fill Type	High Performance film fill 12 mm or 19mm Spacing Cross Fluted (EVAPAK®)	Low Fouling film fill 25 mm Spacing Vertical Fluted (TechClean™)	Anti-fouling film fill 19mm Vertical Flow (VertiClean™)	Splash Fill Bars / Grids (Opti-Bar™ Arch-Bar™ Opti-Grid™)
TTS (ppm)	<25	<50	<100	>100
Bacteria Count (ppm)	<10,000	<100,000	<1,000,000	>1,000,000
Bio & Scale Control	Required	Required	Required	Lower to none


Note: Fill spacing function of TDS

# Film Fill types – Materials – Maintenance

- Types of Fill & Selection Criteria
- **Thermal Performance Ratings**
- Material and Mechanical Properties
- Fill Life Time and Maintaining Tower Efficiency

# Thermal Performance Ratings


## Counterflow Film Fill and Spray Test Cell



1. Forced draft fans
2. Airflow nozzle wall to measure volumetric airflow
3. Turning vanes
4. Cold water collecting troughs and mixing box
5. Counterflow fill test section
6. Hot water distribution pipes and spray nozzles
7. Drift eliminators

# Thermal Performance Ratings

## Counterflow Film Fill and Spray Test Cell




FULL SPECTRUM GLOBAL SOLUTIONS



# Thermal Performance Ratings

- $KaV/L$
- $\Delta P$



Air rate:

1.5 → 5.0 m/s (300-1000 FPM)

Water rate:


45 → 160 m<sup>3</sup>/h (200-700 GPM)

Production testing:

- Film fills
- Drift eliminators
- Splash fills
- Spray nozzles

# Thermal Performance Ratings

## Fill Data



# Thermal Performance Ratings



## Thermal Rating Sheet (CTI Summary)

Rated Using Evap Suite (Version: Debug v  
07/01/2016)

Project Name:	Shuttle Station	Date Rated:	31/03/16
Customer Name:		Date Printed:	31/03/16
Location:		Contact Name:	Andrew T. Cell
Proposal Number:		Contact Phone:	410-758-2000
Selection ID:	0113C38a28 2D 11c3a17c		

<b>Selection Type:</b>		<b>Components</b>	
Drift Type:	Induced Draft	Louver Model:	Wide
Fan Type:	Counterflow	Fill Model:	TechCrown 312 (11/13)
Operation Mode:	Normal	Spray Nozzle Model:	EvapJet 4
Wet / Dry Mode:	Wet Only	Drift Eliminator Model:	CEP400
Slowing Fan - Model#:	Given: HWY, CWY, WBT, WFlow	Inlet Config:	Flat

<b>Geometric Conditions:</b>		<b>Thermal Results</b>	
Tower Elevation:	49 ft 15 m	Predicted HWY:	100.04 °F 42.80 °C
Cell Density:	5	Predicted Range:	14.04 °F 7.83 °C
Cell Length:	38.00 ft 11.582 m	Predicted CWY:	95.00 °F 35.00 °C
Cell Width:	38.00 ft 11.582 m	Predicted Approach:	8.40 °F 3.03 °C
Quantity Fans Per Cell:	1	Predicted Slowing HWY:	89.60 °F 32.00 °C
Basin Yield Offset:	0.50 ft 0.152 m		
Air Inlet Arrangement:	# 2 Air Inlets (HS)		

<b>Geometric Heights</b>		<b>Water Side Results</b>	
Air Inlet Height (TOG):	14.00 ft 4.267 m	Input Water Flow Rate:	35,430 GPM 8,346.97 m <sup>3</sup> /h
Fill Air Toile:	0.00 ft 1.828 m	Predicted Water Flow:	30,400 GPM 8,283.26 m <sup>3</sup> /h
Header Center Line (Cell):	22.00 ft 6.858 m	Predicted Tower Capacity:	100.0 %
Pumphead (EM):	26.00 ft 8.227 m	Water TOC:	--- PPM
Pressure Height:	5.20 ft 1.596 m	Evaporation:	1.30 %
Fan Deck Height:	30.00 ft 9.144 m	Evaporation Rate:	406 GPM 150.78 m <sup>3</sup> /h
Fan Stack Height:	10.00 ft 3.048 m		
Total Height:	40.00 ft 12.192 m		

<b>Fan Information</b>		<b>Airflow</b>	
Fan Manufacturer:	Other	Airflow Per Fan:	901.415 CFM 425.42 m <sup>3</sup> /h
Fan Type:	(Fan Type)		
Fan Model:	---		
Fan Diameter:	20.00 ft 7.925 m		
Fan Blades:	---		
Fan Blade Pitch:	---		
Fan Static Efficiency:	85.0 %		
Fan Total Efficiency:	80.0 %		

<b>Driv Information</b>		<b>System Pressures</b>	
Motor Speed:	1,775 RPM	Fan Static Pressure:	1.032 inWG 257.16 Pa
Drive Model:	1712	VP Fan:	0.171 inWG 42.57 Pa
Drive Ratio (Nom/Actual):	12:1	Fan Total Pressure:	1.203 inWG 299.73 Pa
Fan Speed (Typ):	11,884 RPM		
Fan Speed (RPM):	145.48 RPM		

<b>Power Consumption</b>	
Predicted Fan P. (AMSI):	222.05 HP 166.02 kW

[Warnings] Fill Outside Test Range: Fill AT = 1.325 m.

Confidential Property of EvapTech Inc.

Address: 6371 Norman Road - Lenoir, NC 28544  
Phone: 815-622-6185  
Website: www.evaptech.com



EvapTech, Ask, Profile, Digi, Digi, Digi  
MALAYSIYA  
Phone: 811 688 8876 (7/24)



# Thermal Performance Ratings

- Field data analysis
- Competitive analysis

- $KaV/L$
- $\Delta P$



Item	Value	Unit
1	100	kg
2	200	kg
3	300	kg
4	400	kg
5	500	kg
6	600	kg
7	700	kg
8	800	kg
9	900	kg
10	1000	kg

# Film Fill types – Materials – Maintenance

- Types of Fill & Selection Criteria
- Thermal Performance Ratings
- **Material and Mechanical Properties**
- Fill Life Time and Maintaining Tower Efficiency

# Cooling Tower Heat Exchange Surface

## CTI STD – 136 : Thermoplastic Materials Used for Film Fill, Splash Fill, Louvers and Drift Eliminators

- This CTI specification covers the most common fills, splash fills, louvers, drift eliminators, nozzles, and other small components for use in standard properties, burning properties, and recommended testing procedures employed to determine the defined values, whether processed from virgin or reground material.
- Revised June 2010

# Material and Mechanical Properties

## ASTM E 84

ASTM E 84 tests for flame spread rating (FSR).

- Red oak flooring has FSR of 100
- Fiber cement board has a FSR of 0

Historical number Flame Spread Rating PVC Fills was 25.

Today : material with Flame Spread Rating of 5

# Material and Mechanical Properties

## Film Fill Material Thickness & UV Protection

- Material thickness & UV protection determines life time of the fill
- Specify the fill material thickness “before” and “after forming” !  
The forming process thins the material and  
**15 mills** PVC fill before forming (can) become **10 mills** after forming !

# Material and Mechanical Properties

## Remark

*How we know that specified numbers and qualifications are valid for the materials supplied ?*

Ask specific test reports

# Material and Mechanical Properties

## Materials

### PVC fill

- High strength (CTI STD 136)
- Extremely durable
- Self - extinguishing
- Surface wets – out well
- Can be glued in bundles

### PP fill

- Durable but high creep rate, **need 50 % thicker than PVC**
- **Very Flammable**
- Poor wetting characteristics
- Cannot solvent bond

# Film Fill types – Materials – Maintenance

- Types of Fill & Selection Criteria
- Thermal Performance Ratings
- Material and Mechanical Properties
- **Fill Life Time and Maintaining Tower Efficiency**

# Water Treatment: Scaling

Langelier saturation index: Recommended range



-0.5

0.0

1.0

2.0

Aggressive water

Scaling water



Corrosion inhibitors recommended


Scaling inhibitors or dispersants recommended

Safe zone : Acid

Typical : Limit pH at 8.5-9 maximum

# Fill Life Time and Maintaining Tower Efficiency


## Scale Build-Up on PVC Fill Sheets




- Maintenance :  
Assure fill remains in good condition
- Water treatment important to control scale build-up

# Fill Life Time and Maintaining Tower Efficiency


## Effect of Fouling on Fill & Cooling Tower Performance



Clean Fill  
(48 kg/m<sup>3</sup>)




1.6 mm Fouling  
(448 kg/m<sup>3</sup>)



3,2 mm Fouling  
(848 kg/m<sup>3</sup>)

# Fill Life Time and Maintaining Tower Efficiency

## Estimate of Performance Loss vs. Fouling



# Important Criteria When Considering Cooling Towers For Your DCP

- Film Fill Types – Materials – Maintenance
- **Cooling Tower Layout**
- Thermal Performance Certification (CTI)

# Cooling Tower Layout

- Arrangement
- Type of Enclosures
- Influence on Thermal Performance
- Clearance
- Type of Influence

# Arrangement

## Single Row



# Arrangement

## Back to Back (Double Row)




# Arrangement

**Two Rows – Not Ideal for Recirculation!**



# Arrangement

## Two Rows – Not Ideal for Recirculation!



# Arrangement

Stairway → Space Required!



FULL SPECTRUM GLOBAL SOLUTIONS



# Type of Enclosures

## Free Field Installation



# Type of Enclosures

## Solid Walls Enclosures



# Type of Enclosures


## Louvered Walls Enclosures



- % Free open area louvers
- Pressure drop through louvers
- Orientation

# Type of Enclosures

## Louvered Walls



Effective louver wall height  
=  
1.2 x air inlet height

# Type of Enclosures

## Louvered Walls

- Air flow takes the path of least resistance.
- Equilibrium Point : vertical downward air flow  $\longleftrightarrow$  air flow through louvers


Wall Type	Louver	Solid
Net Vertical Air Velocity $\leq$	600 FPM	400 FPM
Net Louver Air Velocity $\leq$	500 FPM	N/A

# Influence on Thermal Performance

- Net free open area
- Air flow obstruction
  - Enclosure structural framing
  - Piping
  - Walkways
- Clearance

# Clearance


## Case 1



- Minimal impact
- No correction required

# Clearance


## Case 2



- $2 \times \text{air inlet height} < \text{clearance} < \text{air inlet height} + \text{wall height}$
- Add 5 Pa (0.02 in WG)
- Risk for recirculation!


# Clearance

## Case 3



- $1 \times \text{air inlet height} < \text{clearance} < 2 \times \text{air inlet height}$
- Add 10 Pa (0.04 in WG)
- High risk for recirculation!

# Type of Influence



- Increased pressure drop
- Mal-distribution of air
  - Increased static pressure
  - Hot water bypass
- Recirculation
  - Height of enclosure
  - Solid or louvered wall
  - Clearance

# Layout

IF YOU OBSTRUCT THE AIR TO THE COOLING TOWER

THE COOLING TOWER DESIGN / THERMAL  
PERFORMANCE WILL BE AFFECTED

# Important Criteria When Considering Cooling Towers For Your DCP

- Film Fill Types – Materials – Maintenance
- Cooling Tower Layout
- **Thermal Performance Certification (CTI)**

# CTI Standards



- STD-105  
Code/Procedure for CT Thermal Performance Testing on Site
- STD-201  
Certification Program: Thermal Performance of **Packaged CT's**
- STD-202  
Voluntary Program for **Custom/Field Erected** Cooling Towers

# CTI STD-105

- Test Conditions: max. variations
  - Wet-bulb: +/- 8.5°C (15°F)
  - Range: +/- 20%
  - Water flow: +/- 10%
- Instrumentation
- Measurements
- Evaluation of results

# CTI STD-201

- Certification Scope:
  - Wet-bulb: 12.8°C to 32.2°C (55°F to 90°F)
  - Range:  $\geq 2.2^{\circ}\text{C}$  (4°F)
  - Approach:  $\geq 2.8^{\circ}\text{C}$  (5°F)
  - Inlet T:  $\leq 51.7^{\circ}\text{C}$  (125°F)
- Standard models
- Accessories



# CTI STD-202

**NEW**

- Participants allow CTI to publish thermal performance test results
- Field test must be executed by CTI licensed test agency
- Participants:
  - Composite Cooling Solutions, L.P. (CCS)
  - Evaptech Inc. (Evapco Inc.)
  - SPX Cooling Technologies, Inc (Marley)

# CTI STD-202



MARLEY

EvapTech, Inc.  
A wholly owned subsidiary of Evapco, Inc.

Participating Manufacturer	Composite Cooling Solutions, L.P.	EvapTech, Inc.	SPX Cooling Technologies	All Multi-Agency Acceptance Tests for the previous year*
Testing during the Period:	8/21/2013 to 08/16/2016	10/26/2013 to 10/18/2016	05/20/2015 to 08/30/2016	2015
Percentage of tests at or above 100% Capability	N.A.	100	60	62
Percentage of tests at or above 95% Capability	N.A.	100	100	82
Average Capability of tests below 95% Capability	N.A.	None	None	89.4
Average Water Flow Rate	N.A.	74,059	108,282	58,583

N.A. = At the time of this publication the minimum number of CTI licensed tests required to publish results by STD-202 have not been performed.

FULL SPECTRUM GLOBAL SOLUTIONS



## Benefits for Owners/Operators

- Performance tests demonstrate the actual thermal performance
- Lower outlet water temperature → chiller efficiency increases
- More efficient DCP → lower energy consumption

# Innovations for LIFE

- 
- Taking
  - Quality & Service
  - to a Higher Level